

80262.0101

PATENT
US Pat. No. 5,981,957**In The Specification**

Applicant is amending the specification in this patent under 37 CFR 1.173(b) and 37 CFR 1.173(d). These changes include ministerial changes, grammatical changes, and mistakes made by the US PTO during the printing of the patent. Applicant is not adding new matter with these amendments.

Amend the specification with the selected replacement paragraphs on the following pages.

80262.0101

PATENT
US Pat. No. 5,981,957

Paragraph at c. 2, l. 37-54.

In practice, we typically probe many different types of molecules at once with the excitation light pulse. FIG.2 illustrates the case where a single short excitation pulse of light 30 is absorbed by a sample of identical molecules all at once. The fluorescence decay curve 32 resulting from a typical fluorescence response of a sample of identical molecules is exponential in nature because not all of the identical molecules emits its fluorescence photon at precisely the same time. The exponential decay follows a mathematical function so that we can calculate the fluorescence lifetime, τ :

$$I(t) = I_0 \cdot e^{-(t-t_0)/\tau}$$

$$I(t) = I_0 \cdot e^{-(t-t_0)/\tau}$$

where t_0 is the time of the excitation pulse, I_0 is the initial fluorescence and $I(t)$ is the observed fluorescence intensity as a function of time.

80262.0101

PATENT
US Pat. No. 5,981,957

Paragraph at c. 5, l. 30-43.

FIG.5 is a block diagram of the generator component 54 of the present invention for generating the excitation signal. The present invention uses heterodyning techniques to produce two sinusoidal RF signals, a driving/reference signal 90 and a mixing signal 92. The present invention modulates the frequency of the two signals from 10 MHz to 200 MHz. One skilled in the art will appreciate that the present invention could vary the signals over a much larger frequency range. The preferred embodiment of the present invention generates the two signals with a frequency difference of 10 kHz. Another embodiment of the present invention generates the two signals using an adjustable offset frequency where the offset frequency is set through to the present invention's control software.

80262.0101

PATENT
US Pat. No. 5,981,957

Paragraph at c. 11, l. 26-44.

Another, equivalent, way of writing the eigenfunction equations proceeds from the observation that:

$$\mathbf{G} \cdot \mathbf{A}^{-1} = \mathbf{c} \mathbf{c} \quad (23)$$

and

$$\mathbf{S} = \mathbf{c} \mathbf{S} \cdot \mathbf{A} = \mathbf{w} \cdot \mathbf{c} \mathbf{c} \cdot \mathbf{T} \cdot \mathbf{A} \quad (24)$$

so that

$$\mathbf{w}^{-1} \cdot \mathbf{S} \cdot \mathbf{A}^{-1} = \mathbf{c} \mathbf{c} \cdot \mathbf{T} = \mathbf{G} \cdot \mathbf{A}^{-1} \cdot \mathbf{T} \quad (25)$$

or

$$\mathbf{G}^{-1} \cdot \mathbf{w}^{-1} \cdot \mathbf{S} \cdot \mathbf{A}^{-1} = \mathbf{A}^{-1} \cdot \mathbf{T} \quad (26)$$

80262.0101

PATENT
US Pat. No. 5,981,957

Paragraph at c. 13, l. 10-40.

We may interpret the first of Eqns. (36) in terms of its column vectors as the representation of the r vectors of cc in the orthonormal basis of the r vectors of U :

$$c_j = \sum_{i=1}^r U_i P_{ij} \quad (37)$$

where c_j is the j th column of cc , U_i is the i th column of U and P_{ij} is the corresponding element of P_U . From this expression and the linear independence of the c_j and U_i , we see that P_U is invertible. Linear independence of the c_j requires that:

$$\sum_{j=1}^r \alpha_j c_j = 0 \quad \text{only if} \quad \alpha_j = 0 \quad \text{for all } j=1, \dots, r. \quad (38)$$

From Eqn. (36), we see that Eqn. (37) implies:

$$\sum_{i=1}^r U_i P_{ij} \alpha_j = 0.$$

From the linear independence of the U_i , we must have

$$\sum_{j=1}^r P_{ij} \alpha_j = 0, \quad \text{for all } i = 1, \dots, r. \quad (39)$$

80262.0101

PATENT
US Pat. No. 5,981,957

Paragraph at c. 14, l. 1-12.

A second method for solving Eqns. (30) is to use Eqn. (31) to write the pseudo inverse of G :

$$G_{pi} = V \cdot C_i^{-1} \cdot U^T \quad (43)$$

so that we have:

$$G \cdot G_{pi} = U \cdot U^T \quad \text{and} \quad G_{pi} \cdot G = V \cdot V^T,$$

where $U \cdot U^T$ is ~~and~~ an $N \times N$ matrix and $V \cdot V^T$ is an $M \times M$ matrix, and each of these matrices is of rank r .

80262.0101

PATENT
US Pat. No. 5,981,957

Equation 63, c. 15, l. 64.

~~$$\eta = Tr(M_x \cdot U \cdot U^T)$$~~

$$\eta = Tr(M_v \cdot U \cdot U^T)$$

(63)

80262.0101

PATENT
US Pat. No. 5,981,957

Paragraph at c. 17, l. 1-6.

As the frequencies in w are large, we renormalize $\|w^{-1} \cdot Sx\|$ to equal $\|Gx\|$ so as to avoid skewing the results in favor of the Gx data 138. This amounts to a ~~resealing~~ rescaling of the units for the frequencies and the lifetimes. This ~~resealing~~ rescaling of units is compensated once the lifetimes are found, so they are expressed in seconds.

80262.0101

PATENT
US Pat. No. 5,981,957

Paragraph at c. 18, l. 63 to c. 19, l. 16.

FIG.10 illustrates the present invention's ability to identify and discriminate between individual overlapping spectral components in a target mixture. The present invention allows for the extraction of both the individual fluorescence spectra and lifetimes from a target mixture of fluorophores. FIG.10 illustrates the present inventions ability to differentiate spectra using a three-dye mixture of OXAZINE™ 720, 725 and 750. OXAZINE is a trademark of Exciton, Inc. We mixed the dyes at equal concentrations of 3.3 μ M. We recorded the emission spectra for an excitation signal wavelength of 640 nm and the laser modulation frequency was swept (modulated) from 10 MHz to 140 MHz at 5 MHz increments. The present invention extracted fluorescence lifetimes of 3.705 nsec for Oxazine 720 (196 on FIG.10), 1.979 nsec for Oxazine 750 (198 on FIG.10), and 0.5588 nsec for Oxazine 725 (200 on FIG.10). The results from the present invention compared very well with the listed individual dye fluorescence lifetimes of 3.739 nsec for Oxazine 720, 2.014 nsec for Oxazine 750 and 0.9935 nsec for Oxazine 725. The individual spectra extracted for each dye from the mixture revealed spectral characteristics that matched with spectra obtained from the individual dyes.